





1200-UP SERIES

LOW TEMPERATURE HOT HOLDING CABINETS

ecosmart • HALO HEAT...a controlled, uniform heat source that gently surrounds food for better appearance, taste, and longer holding life.

- Holds hot food hot...meat, poultry, fish, potatoes, casseroles, vegetables, rolls, etc.
- Dual purpose both a holding cabinet and dough proofer.
- Universal rack design accommodates standard full-size (gastronorm) pans or full-size sheet pans.
- Can be converted with side racks to accommodate shelves for full size gastronorm pans or full size sheet pans.
- Stainless steel interior resists corrosion.
- Casters provide easy mobility.
- Antimicrobial handle retards the growth of illness-causing pathogens.
- Digital control senses temperature drops faster, providing quick heat
- Door venting holds crispy food better.

Two (2) individually controlled oven compartments are enclosed in one 20 gauge stainless steel exterior and doors. Each controlled compartment has one (1) Simple Control with ON/OFF power switch; Up and Down Arrow Keys with a temperature range of 60° to 200°F (16° to 93°C); indicator light, and digital display. Each compartment is equipped with two (2) universal side rails and four (4) sets of chrome plated pan slides designed to accommodate standard full-size pans. Pan supports are adjustable in sixteen (16) positions on 1-3/4" (44mm) centers, and one (1) set of 5" (127mm) heavy duty casters – 2 rigid and 2 swivel with brake.

☐ **MODEL 1200-UP** Double compartment holding cabinet

DELUXE CONTROL OPTION



- ☐ Solid state electronic control option simplifies temperature setting and has a clear, easy-to-read LED display and includes our patented SureTemp™ heat recovery system. SureTemp™ reacts immediately to compensate for any loss of heat whenever the door is opened.
- ☐ Deluxe control is also available with six independent multiple timers for each compartment to facilitate "first-in, first-out" concept.
- ☐ Deluxe control with internal temperature probe.





FACTORY INSTALLED OPTIONS

- Electrical Choices
 - □ 120
 - □ 208-240 (2000W)
 - □ 208-240 (4000W)
 - □ 230 (2000W)

⇒ Specify Voltage:

- □ 230 (4000W)

- Cabinet Choices
 - **⇒** Specify Cabinet:
 - ☐ Reach-In, standard
 - ☐ Pass-Through, optional

- Door Choices
 - **⇒** Specify Door:
 - ☐ Solid Door, standard ☐ Window Door, optional
 - **⇒** Specify Door Swing:
 - ☐ Right-hand swing, standard ☐ Left-hand swing, optional
 - Note: Pass-through cabinets

cannot have all doors hinged on the same side.

ADDITIONAL FEATURES

- Side Rack Model
 - ☐ As an alternative to universal pan slides, this unit can be ordered as a "side rack" model which is equipped with two (2) side racks



and three (3) chrome plated wire shelves. It will accommodate full and half size US hotel and European gastronorm pans on the side racks, or sheet pans on shelves.



W164 N9221 Water Street • P.O. Box 450 • Menomonee Falls, Wisconsin 53052-0450 • U.S.A. PHONE: 262.251.3800 800.558.8744 U.S.A./CANADA FAX: 262.251.7067 800.329.8744 U.S.A. ONLY






75-13/16" (1924mm) — with 5" (127mm) casters*

1200-UP SERIES

LOW TEMPERATURE HOT HOLDING CABINETS





PRODUCT\PAN CAPACIT	TY (PER COMPART	MENT)	
192 lbs (87kg) maximum •	VOLUME MAXIMUM: 120	QUARTS (152 LITERS)	
Pan slides (2 per set) - 1-3/4 (4	4mm) centers		
Pan Size	Four (4) sets of pan slides provided	Maximum capacity with additional pan slides	
FULL SIZE: 20" x 12" x 2-1/2" GN1/1: 530mm x 325mm x 65mm	Eight (8) pans - 2 per set of slides	Sixteen (16) pans - with 4 additional sets of pan slides	
FULL SIZE: 20" x 12" x 4" GN1/1: 530mm x 325mm x 100mm	Eight (8) pans - 2 per set of slides	NO ADDITIONAL CAPACITY	
FULL SIZE: 20" x 12" x 6" 530mm x 325mm x 150mm	Eight (8) pans - 2 per set of slides	NO ADDITIONAL CAPACITY	
FULL SIZE SHEET PANS: $18" \times 26" \times 1"$	Four (4) pans - 1 per set of slides	Sixteen (16) pans - with 12 additional sets of pan slides	
Side Racks and Shelves			
Pan Size	Three (3) shelves provided	Maximum capacity with additional shelves	
FULL SIZE: 20" x 12" x 2-1/2" GN1/1: 530mm x 325mm x 65mm	Sixteen (16) pans - 2 per side rack	NO ADDITIONAL CAPACITY	
FULL SIZE: 20" x 12" x 4" GN1/1: 530mm x 325mm x 100mm	Eight (8) pans - 2 per side rack	NO ADDITIONAL CAPACITY	
FULL SIZE: 20" x 12" x 6" GN1/1: 530mm x 325mm x 150mm	Eight (8) pans - 2 per side rack	NO ADDITIONAL CAPACITY	
FULL SIZE SHEET PANS: 18" x 26" x 1"	Three (3) pans -	Eight (8) pans with 5	

1 per shelf

DIMENSION	DIMENSIONS: HxWxD			
EXTERIOR:	75-13/16" x 25-1/16" x 32-3/16"			
	(1924mm x 636mm x 817mm)			
PASS-THROUGH:	75-13/16" x 25-13/16" x 33-13/16"			
	(1924mm x 655mm x 858mm)			
INTERIOR EACH COMPARTMENT:				
28-3/4" x 21-5/16" x 26-1/2" (730mm x 541mm x 673mm)				

32-3/16" (817mm)

INSTALLATION REQUIREMENTS

- Oven must be installed level.
- The oven must not be installed in any area where it may be affected by steam, grease, dripping water, extreme temperatures, or any other severely adverse conditions.
- Appliances with casters and no cord or plug must be secured to the building structure with a flexible connector. NOT FACTORY SUPPLIED.

CLEARANCE REQUIREMENTS				
BACK: 3" (76mm)	тор: 2" (51mm)	SIDES: 1" (25mm)		

ELECTRICAL						
	VOLTAGE	PHASE	CYCLE/HZ	AMPS	кW	CORD & PLUG
120	120	1	60	16.0	1.9	NEMA 5-20P, 20A-125V PLUG
- 240 2000W	208 240	1 1	60 60	7.0 8.0	1.4 1.9	NEMA 6-15P, 15A-250V PLUG (USA ONLY)
208 4000W	208 240	1 1	60 60	14.0 16.0	2.9 3.8	NO CORD OR PLUG
230	230 2000W 230 4000W	1 1	50/60 50/60	7.7 15.4	1.8 3.5	CEE 7/7, 220-230v PLUG

additional shelves

WEIG	WEIGHT					
NET:	333 lb (151g)	SHIP: (EST.) 393 lb (178 kg)				
CARTON DIMENSIONS: (L x w x H) 35" x 35" x 82" (889mm x 889mm x 2083mm)						

OPTIONS & ACCESSORIES			
☐ Bumper, Full Perimeter	5012932	☐ Drip Pan with Drain 1-11/16" (43mm)	5014448
☐ Casters, 3-1/2" (76mm) - 2 RIGID, 2 SWIVEL W/ BRAKE	5008017	☐ Security Panel with Lock	5013936
☐ Door Lock with Key (EACH HANDLE)	LK-22567	☐ Shelf, Stainless Steel	SH-23738
☐ Handle Kit, Push/Pull (SET OF FOUR)	55662	☐ Shelf, Chrome Plated	SH-2733
		☐ Universal Pan Slides, Chrome Plated	SR-24447
☐ Legs, 6" (152mm), Flanged (SET OF FOUR)	5011149	☐ Universal Pan Slides, Stainless Steel	SR-24762
☐ Pan Grid, Chrome Plated, Wire	PN-2115	☐ Water Reservoir Pan (FOR PROOFING)	1775
PAN INSERT 18" x 26" (457mm x 660mm x 25mm	n)	□ Water Reservoir Pan Cover	1774



W164 N9221 Water Street • P.O. Box 450 • Menomonee Falls, Wisconsin 53052-0450 • U.S.A. PHONE: 262.251.3800 800.558.8744 U.S.A./CANADA

FAX: 262.251.7067 800.329.8744 U.S.A. ONLY

