

Carson, CA 90746 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

| Project : | |
|----------------|------|
| Model #: | |
| Item #: | Qty: |
| Available W/H: | |
| Approval: | |

Ice Merchandisers

Ice Merchandisers Glass Door Merchandisers

Model: TGIM-49

DIGITAL TEMPERATURE CONTROL SYSTEM Provides precise and constant temperature. This level of precision allows food products to remain fresh over an extended period of time.

HIGH-TECH MONITOR

The unit will beep if the door has been opened for more than 30 seconds. The monitor digitally displays the present temperature and current status of the freezer. You can easily change the temperature by adjusting the thermostat.

■ EFFICIENT REFRIGERATION SYSTEM

Turbo Air's freezers are designed with oversized and balanced (CFC Free R-404A) refrigeration systems. These include efficient evaporators and condensers for faster freezing and greater efficiency.

AUTOMATIC EVAPORATOR FAN MOTOR DELAYS

Through stopping the evaporator fan when the freezer door opens, the circulation of hot, moist air into the freezer is prevented. This increases energy efficiency and lengthens the life of the compressor.

■ ICE DOES NOT MELT EVEN IN HOT CLIMATES

Turbo Air ice merchandisers are based on a freezer system which is adjusted to the ideal temperature range for bagged ice storage, whereas our competitors use refrigerator based systems. It maintains an avg. temperature of 12°F or below and eliminates ice melting problems during hot weather conditions.

LED LIGHTING INTERIOR DISPLAY SYSTEM

Brighter and longer lasting LED lights provide attractive, enhanced illumination compared to fluorescents.It saves energy by producing less heat, while maximizing the visibility in the display area.

■ TRIPLE PANE HEATED GLASS DOORS WITH HEAT REFLECTING FILM

Equipped with unique triple pane heated glass doors with a layer of patented, transparent thermal insulating film applied between the glass layers. Lightweight door construction reduces door maintenance and roller wear, and facilitates smooth door opening.

HIGH-DENSITY POLYURETHANE INSULATION

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

■ MAGNETIC DOOR GASKETS

Magnetic door gaskets are of one piece construction, removable without tools for ease of cleaning and replacement.

■ BOTTOM MOUNT COMPRESSOR UNITS

Turbo Air's bottom mount compressor allows easier access for service and extra storage space above. In addition, the lower area provides a cooler and less greasy operating environment which results in reduced compressor running time.



FREEZER HOLDS 10°F~15°F FOR THE **BEST IN BAGGED ICE STORAGE**











| Model Swing Door CU./FT. HP AMPS Crated Weight (lbs.) L x D*x H (inches) | ľ | TGIM-49 | 2 | 46.2 | 2/3 | 9.0 | 505 | 541/2 x 303/8 x 767/8 |
|---|---|---------|---|---------|-----|------|-----|-----------------------|
| | | Model | | CU./FT. | НР | AMPS | | l I |

Ice Merchandisers

Model: TGIM-49


| ELECTRICAL DATA | TGIM-49 | | | | |
|-------------------------|------------------|--|--|--|--|
| Voltage [†] | 115/208~230/60/1 | | | | |
| Plug Type† | © NEMA L14-20 | | | | |
| Full Load Amperes | 11 | | | | |
| Compressor HP | 11/2 | | | | |
| Cord Length ft. | 7 | | | | |
| Refrigerant | R-404A | | | | |
| DIMENSIONAL DATA | | | | | |
| # of Doors | 2 | | | | |
| Net Capacity cu. ft. | 49 | | | | |
| Ext. Length Overall in. | 543/8 (1382mm) | | | | |
| Ext. Depth Overall in.* | 293/4 (756mm) | | | | |
| Ext. Height Overall in. | 77 (1956mm) | | | | |
| Int. Length Overall in. | 501/2 (1283mm) | | | | |
| Int. Depth Overall in. | 261/8 (665mm) | | | | |
| Int. Height Overall in. | 601/8 (1525mm) | | | | |
| Gross Weight lbs. | 587 | | | | |
| Net Weight lbs. | 554 | | | | |


Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

- WARRANTY: 2 Year Parts and Labor Warranty
 Additional 3 Year Warranty on Compressor
- 4" SWIVEL CASTERS AVAILABLE (OPTIONAL)
- INTERIOR FLOOR RACK AND BACKGUARD STANDARD FOR **OPTIONAL AIRFLOW**
- WHITE PAINTED INTERIOR WITH STAINLESS STEEL TOP AND **FLOOR**
- Non-Peel, Durable Anti-Rust White Painted Exterior WITH GALVANIZED STEEL TOP

PLAN VIEW (unit: inch)





Ver.201301







Turbo air











■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519 ■ Warranty: 800-381-7770 ■ AC: 888-900-1002

^{*} Depth does not include 1-3/8" for glass door handles.

[†]TGIM-49 requires dual voltage 115/208~230V (NEMA L14-20)